




INSTALLATION AND OPERATING INSTRUCTIONS

TWT-MUC-101 • TWT-MUC-102 • TWT-MUC-103



Email: info@triangularwave.com • triwaveinc@aol.com • Websites: www.Triangularwave.com • www.twtwatertreatment.com

CONGRATULATIONS!

With your purchase you have Guaranteed your family a source of pure, fresh tasting water. With proper care and maintenance your TWT-MUC-101, 102 or 103 should last you for a lifetime.

Please take time and read the following suggestions before installation.

INSTALLATION AND OPERATING INSTRUCTIONS **TWT-MUC-101, TWT-MUC-102, TWT-MUC-103**

INSTALLATION INSTRUCTIONS:

1. Turn off the cold water supply under the sink.
2. Install the saddle valve, supplied with unit, on the cold water line.
3. Mount the water spout, supplied with unit, on the counter top by using the existing hole or by drilling a new hole with a 7/16" drill bit.
4. Place your TWT unit in the desired position, under your sink.

Note: Water in / water out

BE CAREFUL NOT TO KINK THE TUBING



MUC-103 shown above

5. Cut the tubing to the desired length and smooth away any edges.
6. After fastening all the tubing in place slowly turn on the water supply.
7. Open the saddle valve by turning the handle counter clockwise.
8. Watch for leaks. If there are any leaks tighten the saddle valve fittings, immediately before the leak, until it stops.
9. Allow filter to operate 10 full minutes before using.

KDF-GAC CARTRIDGE REPLACEMENT:*

The KDF-GAC Filtration cartridge in your TWT-MCT-101 represents the "State of the Art", in home water treatment. It will remove 98%+ contaminants for at least 7500 gallons. After 7500 gallons we recommend changing your cartridge. The Water Quality Association states that an average family of four uses 3000 gallons a year at the kitchen faucet. In order to maintain peak effectiveness, we recommend replacing your filter once a year.

MAINTENANCE:

Triangular Wave Technologies, Inc. offers an optional patented Meter Valve. The Meter Valve is pre-set at the factory for 3,500 gallons. After 3,500 gallons the Meter Valve will shut the unit off, protecting you from exceeding the unit's capacity, reset your Meter Valve each time until you reach 7500 gallons or one year, whichever comes first. Prior to your last setting call your TWT Distributor to order your replacement cartridges. This will ensure the continued proper operation of your system.

* Includes appropriate wrench for easy replacement.

Email: info@triangularwave.com • triwaveinc@aol.com • Websites: www.Triangularwave.com • www.twtwatertreatment.com