



TWT-SYSMD-1400

Product Information



















Technical Specifications

Flow Range (limited by filter selection):

Initial UV Dose at Max. Flow (95% UVT):

Electrical:

Replacement Lamp:

Ballast:

Filtration (2 Stages): Stage 1, Sediment Filter: Stage 1, Carbon Filter: Electronic Descaler:

Max. Operating Pressure:

Plumbing:

Shipping Size and Weight:

Up to 53 litres per minute (14 GPM) 3,180 litres/hour, 76.3 m³/day (840 gallons/hour, 20,160 gallons/day) 40 mJ/cm² (40,000 µWsec/cm²) @ 14 GPM 110-130 Volt AC or 210-250 Volt AC, 50-60 Hz Low-Pressure UV Lamp, Part # RL-51/540T5 Electronic Ballast w/ Lamp Out Alarm, Power LED, Running Days Countdown (Resettable) Model RH51-800-95L (part # BE-80014/30-ECO 10" BigBlue (L 10", OD 4-1/2") w/ Pressure Relief Polypropylene/Polyester Pleated Cell, 5 Micron Carbon Impregnated Pleated Cell, 10 Micron TWT401

Pre-Wrapped, PVC Sch80 Reaction Chamber

90 psi - 6.2 bar 1" MNPT In/Out

Crate 33x33x10 inches, 97 lbs

Specifications are subject to change



Limited Time: Free Crating & Free Shipping! Limited Time Bonus: Free Replacement Filters with P.O. Special Pricing: \$3,800 (offer expires Jan. 31st, 2022)



Contact us with your order or questions

Phone: 1-800-SAVE H20 (1-800-728-3420)

Email: info@twtwatertreatment.com